

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
20 January 2005 (20.01.2005)


PCT

(10) International Publication Number  
WO 2005/005126 A2

- (51) International Patent Classification<sup>7</sup>: B29C 45/14 (74) Agent: KLINGSEISEN, Franz; Bräuhäusstrasse 4, 80331 München (DE).
- (21) International Application Number: PCT/EP2004/007687
- (22) International Filing Date: 12 July 2004 (12.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
103 31 519.5 11 July 2003 (11.07.2003) DB
- (71) Applicant (for all designated States except US): HEKUMA GMBH [DE/DE]; Freisinger Str. 3b, 85386 Eching (DE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): KNÖPFLE, Kurt [DE/DE]; Diessener Str. 2, 80638 München (DE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: HANDLING SYSTEM FOR AN INJECTION MOLDING MACHINE AND METHOD FOR INSERTING AN APPLICATION IN THE INJECTION MOLD



(57) Abstract: A handling system for an injection molding machine is presented wherein an application, for example a label, is inserted in the mold cavity (105) of an injection molding tool (104) before injection molding, when for example a beaker having the label (1) on the outer circumference is fabricated by injection molding, wherein a preform means (8) for the label (1) is provided outside the injection molding tool, has a feeder means (3, 4) for the label and a preform (5) into which the label is introduced by the feeder means, and is thus preformed to the shape in which it is to be inserted in the injection mold (105), and a transfer means (302) removes the preformed label from the preform (5) and delivers it to the injection mold (105), wherein the preform (5) is decouplable from the feeder means (3, 4) and moveable into a position different from it.

BEST AVAILABLE COPY

WO 2005/005126 A2

WO 2005/005126 A2



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- without international search report and to be republished upon receipt of that report

**BEST AVAILABLE COPY**